



Notes:

1. Raceway of inner & outer ring induction hardened. hardness: 55~62HRC
Depth ≥ 3.5mm
2. Inner & outer ring quenched & tempered, hardness: 207~262HB

Gear Data					Design		Check		Model																												
Module	m	14	Gear heat treatment requirements		Date		Approve		111.32.1600		Weight	440kg																									
Teeth no	z	127	HRC		Qty	Size	Axial clearance	0.02~0.07	Name		Slewing Bearing	Qty	Scale																								
Teeth pressure angle	α	20°	Precision (GB10095-88)	10	Inner ring mounting hole	45	Φ26	Radial clearance	0.02~0.07	Material		50Mn	Total 1 page	The 1st page																							
Modification coefficients	x	+0.5			Outer ring mounting hole	45	Φ26	machine tolerances without notes																													
Reduction coefficients	km	1.4			Oil hole	5	M10×1	<table border="1"> <tr> <td>≤200</td> <td>≤500</td> <td>≤710</td> <td>≤1120</td> </tr> <tr> <td>±0.30</td> <td>±0.40</td> <td>±0.50</td> <td>±0.65</td> </tr> <tr> <td>≤1600</td> <td>≤2000</td> <td>≤2500</td> <td>≤3150</td> </tr> <tr> <td>±0.80</td> <td>±0.95</td> <td>±1.10</td> <td>±1.35</td> </tr> <tr> <td>≤4000</td> <td>≤5000</td> <td></td> <td></td> </tr> <tr> <td>±1.65</td> <td>±2.0</td> <td></td> <td></td> </tr> </table>						≤200	≤500	≤710	≤1120	±0.30	±0.40	±0.50	±0.65	≤1600	≤2000	≤2500	≤3150	±0.80	±0.95	±1.10	±1.35	≤4000	≤5000			±1.65	±2.0		
≤200	≤500	≤710	≤1120																																		
±0.30	±0.40	±0.50	±0.65																																		
≤1600	≤2000	≤2500	≤3150																																		
±0.80	±0.95	±1.10	±1.35																																		
≤4000	≤5000																																				
±1.65	±2.0																																				
Pitch diameter	d	1778			Technical processing standards without notes according to ...JB/T2300-2011																																
					T: Pul location		S: Soft zone		Y: Oil hole		Z: Lifting hole		<p>XUZHOU WANDA SLEWING BEARING CO.,LTD</p> <p>XZWD 万达 Fax: +86 516 83309366 Fax: +86 516 83915766 http://www.slew-bearing.com</p>																								